



PC Board Layout



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 50Hz or 60Hz, 1MIN.

MECHANICAL:

1. HOUSING & INSERT MATERIAL : PBT UL94V-0.
2. CONTACT MATERIAL : DIAMETER 0.45MM PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
3. MATING/UNMATING FORCE : 2.2KG. F MAX.
4. RETENTION STRENGTH : 7.7KG. F MIN BETWEEN JACK AND PLUG.
5. OPERATING LIFE : 600 CYCLES MIN.

ENVIRONMENTAL:

1. STORAGE : -10°C ~ +40°C RELATIVE HUMIDITY<70%.
2. OPERATION : -40°C ~ +70°C.

Remark:

1. Tolerances Unless Otherwise Specified  
 .0±0.25 .00±0.20 .000±0.10
2. The mark with ★ is the key inspection dimension for QC

TELL	0769-81585156		Http://www.coorle.cn		© 库乐科技		
Fax	0769-81605156						
Units	MM	Drawing		Material	Name	5622 10P8C 1X2	
Scale	1 : 1	Check	黄婷				
Rev'	A / 1	Approval		HOUSING	PBT	Part Number	CL562210P8C1*2
View		Date		PIN	Qsn6.5-0.1	File Name	