









記號 MARK	ECN NO.	日期 DATE	修改 DRAW	核准 APPROVE



SPECIFICATION NOTES:

ELECTRICAL:

- 1.VOLTAGE RATING: 125 VAC RMS
- 2.CURRENT RATING: 1.5 AMP
- 3.CONTACT RESISTANCE: 20mΩ MAX.
- 4.INSULATION RESISTANCE: 1000MΩ MIN. AT500V DC.
- 5.DIELECTRIC STRENGTH: 1000 V AC OR 1500V DC RMS AT 0.5mA 50 Hz / 60 Hz FOR 1MINUTE

MECHANICAL:

- 1.HOUSING:PBT+25%GF, HB
- 2.CONTACT:PHOSPHOR BRONZE T=0.25MM
- 3.PLATING:GOLD PLATING G/F AT CONTACT AREA, MATTE TIN AT TAIL 80U MIN., NICKEL 30U MIN. OVER ALL.
- 4.SHELL:BRASS T=0.20
- 5.OPERATING LIFE:750 CYCLES MIN.
- 6.MATING/UNMATING FORCE: 30N/3.06KgF MAX.
- 7.RETENTION STRENGTH:50N OR 30N MIN.FOR 60S±5S

ENVIRONMENTAL:

- 1.STORAGE:-40°C TO +85°C RELATIVE HUMIDITY<80%
- 2.GUARANTEE PERIOD:12 MONTHS
- 3.OPERATION: -40°C TO +85°C

Coorle Technology

<input checked="" type="checkbox"/> 屏蔽壳 Shell <input checked="" type="checkbox"/> 黄铜 Brass Au: <input type="checkbox"/> G/F" <input type="checkbox"/> 1u" <input type="checkbox"/> 3u" <input checked="" type="checkbox"/> Ni <input type="checkbox"/> 80u"	1
胶壳 <input type="checkbox"/> PBT <input type="checkbox"/> LCP	1
金片 (PIN针) <input type="checkbox"/> 黄铜 <input type="checkbox"/> 磷铜 Contacts Brass Phosphor copper <input type="checkbox"/> G/F" <input type="checkbox"/> 1u" <input type="checkbox"/> 3u" <input type="checkbox"/> 6u" <input type="checkbox"/> 15u" <input type="checkbox"/> 30u" <input type="checkbox"/> 50u" <input type="checkbox"/> OTHER	8

品名规格 DESCRIPTION	RJ45 焊线式母座 10P10C 屏蔽 C款			页次 SHEET	1/1
产品编号 PRODUCT NO	单位 UNIT	mm	比例 SCALE	1:1	版本 EDITI
DIMENSION IN mm (Inch) TOLERANCE UNLESS OTHERWISE SPECIFIED		第三视角法 THIRD ANGLE PROJECTION	制图 DRAWN	日期 DATE	2022. 6. 25
x.xx ±0.2	ANGLES		核对 CHECK	日期 DATE	2022. 6. 25
x.xxx ±0.10	X'±0'		批准 APPRO	日期 DATE	2022. 6. 25
x.xxx ±0.050	X'±0.0'				