



与铁脚共面，且同
正同负需要公差内

- Electrical:
- 1.Voltage Rating: 125 Vac Rms
 - 2.Current Rating: 1.5 Amp
 - 3.Contact Resistance: 40 Milliohms Max
 - 4.Insulation Resistance: 1000 Megohms Min@500 Vdc
 - 5.Dielectric Strength: 1000 Vac Rms 60Hz,1Min

- Mechanical:
- 1.Operating: 750 Cycles Min

- Environmental:
- 1.Storage: -40°C To +85°C
 - 2.Opertion: -20°C To +75°C

Mates With Modular Plug Conforming To FCC Part 68,Subpart F

Notes:
MATERIALS

HOUSING: HIGH TEMP. THERMOPLASTIC FLAMMABILITY
UL 94V-0

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT
TIN PLANTING OVER NICKEL IN SOLDER AREA

| | | | | | | | | | |
|--------------------------------------|--------|----------------|------------|----------|-------------------------------------------------------|-------|------|------|------------------------------------------------------------------|
| TOLERANCE UNLESS OTHERWISE SPECIFIED | | CUSTOMER COPY | | | Coorle Technology | | | | |
| LINER | ANGLES | PROJECTION | | | PROD. TOP ENTRY PCB JACK DESCRIP. (6P6C SMT无台阶带L脚) | | | | |
| 0 ± 0.50 | ± 3' | | | | PROD. NUMBER | | | | |
| .0 ± 0.38 | | | | | | | | | |
| .00 ± 0.25 | | DESIGN | PAUL HUANG | 12/26/25 | UNIT | SCALE | SIZE | REV. | Http://www.coorle.cn Tel: 0769-81585156 Fax: 0769-81605156 |
| APPRO. | | | | | MM | / | A4 | D | |

ROHS