





REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	CHKD



PC Board Layout
Component Side Shown

NOTES:

MATERIAL :

- 1. HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE Ø0.46mm.
- 3. PLATING : GOLD PLATING OVER NICKEL.

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500V DC .
- 5. DIELECTRIC WITHSTANDING RESISTANCE : 1000V AC RMS 50Hz. 1MIN.

MECHANICAL:

- 1. DURRABILITY : 750 CYCLES MIN.
- 2. PCB RETENTION PRE-SOLDER : 1 LB MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40°C~+85°C
- 2. OPERATION : 0°C TO 70°C.

DEFINED LISTE	MM (INCH)	DFTD: SHB	DATE: 2007.05.03	<h1>Coor le Technology</h1>
	TOLERANCES EXCEPT AS NOTED	CHKD: LANBO	DATE: 2007.05.03	
	MM	MFG:	DATE:	
	.0 ± 0.15 ±	APPVL:	DATE:	
.00 ± 0.075 ±	MATERIAL :			
.000 ± 0.05 ±	ANGLES ± 0.5	QTY :		
THIRD ANGLE PROJECTION		FINISH :		
		SCALE :		

TITLE		SIZE	REV
5921 1x4 JACK W/O SHIELD		A3	0
DRAWING NO. TES9A1008			
/PART NO.			
DO NOT SCALE DRAWING		SHEET X	OF Y

H
G
F
E
D
C
B
A