

- Electrical:**
- 1.Voltage Rating: 125 Vac Rms
  - 2.Current Rating: 1.5 Amp
  - 3.Contact Resistance: 40 Milliohms Max
  - 4.Insulation Resistance: 1000 Megohms Min@500 Vdc
  - 5.Dielectric Strength: 1000 Vac Rms 60Hz,1Min

- Mechanical:**
- 1.Operating: 750 Cycles Min

- Environmental:**
- 1.Storage: -40°C To +85°C
  - 2.Opertion: -20°C To +75°C

Mates With Modular Plug Conforming To FCC Part 68,Subpart F

**Notes:**


**MATERIALS**

HOUSING: ENGINEERING THERMOPLASTIC FLAMMABILITY UL 94V-0

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT  
TIN PLANTING OVER NICKEL IN SOLDER AREA

SHIELD: BRASS PLATING NICKEL ALLOY

TOLERANCE UNLESS OTHERWISE SPECIFIED		CUSTOMER COPY			Coorle Technology			
LINER	ANGLES							
0 ± 0.50	± 3'	PROJECTION 			PROD. TOP ENTRY PCB JACK DESCRIP. (8P8C屏蔽CAT5脚长2.3)			
.0 ± 0.38					PROD. NUMBER			
.00 ± 0.25								
DESIGN	PAUL HUANG	6/15/19	UNIT	SCALE	SIZE	REV.	Http://www.coorle.cn Tel: 0769-81585156 Fax: 0769-81605156	
APPRO.			MM	/	A4	C		

ROHS