

- Electrical:**
- 1.Voltage Rating: 125 Vac Rms
  - 2.Current Rating: 1.5 Amp
  - 3.Contact Resistance: 40 Milliohms Max
  - 4.Insulation Resistance: 1000 Megohms Min@500 Vdc
  - 5.Dielectric Strength: 1000 Vac Rms 60Hz,1Min
- Mechanical:**
- 1.Operating: 750 Cycles Min
- Environmental:**
- 1.Storage: -40°C To +85°C
  - 2.Opertion: -20°C To +75°C

Mates With Modular Plug Conforming To FCC Part 68,Subpart F

Notes:


MATERIALS

HOUSING: HIGH TEMP. THERMOPLASTIC FLAMMABILITY UL 94V-0

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT  
TIN PLANTING OVER NICKEL IN SOLDER AREA

ROHS

TOLERANCE UNLESS OTHERWISE SPECIFIED		CUSTOMER COPY			Coorle Technology				
LINER	ANGLES				PROD. EMBEDDED PCB JACK				
0 ± 0.50	± 3'				DESCRIP. (4P4C SMT带金属脚)				
.0 ± 0.38					PROD. NUMBER				
.00 ± 0.25		DESIGN	Paul Huang	6/23/10	UNIT	SCALE	SIZE	REV.	Http://www.coorle.cn
		APPRO.			MM	4/1	A4	A	Tel: 0769-81585156 Fax: 0769-81605156