







REV.	MATTER	APP.	DATE
A			
B			



- PCB LAYOUT

NOTE:

1.MATERIAL:

- a.HOUSING:THERMOPLASTIC GLASS FIBRE UL94V-0
- b.CONTACT:BRASS T=0.25mm
(SURFACE PLATING:au^u+Sn100u^u+Ni50u^uMin)
SEE ORDERING INFORMATION
- c.CRUST: T=0.30mm
(SURFACE PLATING:Ni100u^u~120u^u)
SEE ORDERING INFORMATION

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -55° C~ +85° C

Coorle Technology

TOLERANCE		DRAWN	UNIT: MM	TITLE: USB AM 180 SMT 弯脚普通型	
LINEAR	ANGLE			PART NO.	REV.
x. ±1	x' ±5'	APPROVED	SCALE:	1/1	DWG. NO.
.x ±0.38	.x' ±2'	DATE 2010.10.10	SIZE: A4		SHEET. 1 OF 1
.xx ±0.20	.xx' ±1'				
.xxx ±0.10					