

RECOMMENDED P.C.B. PATTERN LAY OUT

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: **Current Rating**
1.5A/contact terminal
2. 额定电压: **Voltage Rating**
30V DC
3. 接触阻抗: **Contact Resistance**
30 milliohms MAX
4. 耐电压: **Dielectric Withstanding Voltage:**
500 V AC AT Sea Level
5. 绝缘阻抗: **Insulation Resistance:**
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: **Connector Mate and Unmate Force**
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
2. 端子保持力: **Terminal Retention**
1.2kgf(MIN)


原材料: Material:

1. 塑胶: **Housing:**
High Temperature Thermoplastics,
PBT White/Black
2. 端子: **Contact: Copper Alloy C2680**
3. 外壳: **Shell: Copper Alloy C2680/SPCC**

电镀: Finish:

1. 端子: **Contact: Plated Gold in Mating Area;**
Tin On Solder Tails
2. 外壳: **Shell: Nickel Plating**

Coorle 库乐科技

UNLESS OTHERWISE SPECIFIED TOLERANCE .X ±0.20 .XX ±0.15 .XXX ±0.10 ANG +2°	DRAWN H.Q.huocv	 TITLE USB AF 双层直插17.0MM弯脚	REV. A	
	APPROVED			UNIT MM
	DATE 2011 03.18	SCALE 3/1	PART NO.	
		SIZE A4	DOC. NO.	